

Product data sheet

Characteristics

8903SMW61V02

combo lighting, electrical held, 3P, 30A, 600V
fuse, NEMA 4/4X, 120/110V 60/50Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product	Combination electrically held lighting contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Disconnecter device type	Fusible disconnect switch R, 30 A 600 V
Electrical connection	Lugs
Height	24.76 in (629 mm)
Depth	8.35 in (212 mm)
Width	9.49 in (241 mm)

Environment

Enclosure Type	NEMA 4/4X brushed stainless steel surface none
Product certifications	UL listed file E16151 CCN NRNT

Ordering and shipping details

Category	21325 - 8903 S (NOT S*C) ELECT.
Discount Schedule	CP1
GTIN	00785901764915
Package weight(Lbs)	15.13 kg (33.36 lb(US))
Returnability	Yes
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------