

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

### Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	45 A
Number of Poles	2P
Number of Phases	1 phase
Horsepower Rating	3 HP 115 V AC 7.5 HP 230 V AC
Maximum Voltage Rating	600 V AC
Control Units	2 momentary push-buttons (START-STOP)
Thermal overload type	Melting alloy 1
Electrical connection	Screw clamp terminals
NEMA size	2
Height	12.68 in (322 mm)
Depth	6.30 in (160 mm)
Width	7.80 in (198 mm)

### Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	NEMA CSA UL listed

### Ordering and shipping details

Category	21192 - 8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	00785901899792
Package weight(Lbs)	4.20 kg (9.25 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Re-productive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------