8736SDA1V02S

Reversing Starter Size 2, 3-Pole, Melting Alloy Overload, NEMA 12 +Options

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Product	Starter
Туре	S
Control Circuit Type	Separate control circuit

Complementary

Complementary		
Control Circuit Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Starter Type	Reversing	
Number of Poles	3P	
Phase	3 phase	
Current Rating	45 A	;
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Thermal overload type	Melting alloy 3	
Electrical connection	Screw clamp terminals	
NEMA size	2	
Height	15.98 in (406 mm)	
Depth	7.87 in (200 mm)	
Width	14.88 in (378 mm)	

Environment

Enclosure Type	NEMA 12 painted sheet steel
Product certifications	CSA
	UL listed
	NEMA

Ordering and shipping details

21272 - 8702,36 SC,SD(NOT S*R,T,W)	
CP1	
00785901163398	
10.08 kg (22.23 lb(US))	
No	
MX	
	CP1 00785901163398 10.08 kg (22.23 lb(US)) No

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	10 months
warranty	16 MONUS
•	