


Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product	Load Center Interior
Marketing Trade Name	QO

Complementary

Load Center Type	Main lugs
Line Rated Current	125 A
Number of spaces	20
Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	24
Maximum Number of Tandem Breakers	4
Number of Phases	1 phase
Wire Size	AWG 4...2/0 kcmil copper or aluminium
Wiring configuration	3-wire
Tightening torque	5.65 N.m (50 lbf.in) AWG 6...AWG 2/0)




Environment

Ambient air temperature for operation	23 °F (-5 °C) 104 °F (40 °C)
Product certifications	UL listed

Ordering and shipping details

Category	00909 - MOUNTING BASES, S/N
Discount Schedule	DE3A
GTIN	00785901804673
Package weight(Lbs)	0.68 kg (1.5 lb(US))
Returnability	No
Country of origin	US

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

China RoHS Regulation	 China RoHS Declaration
Circularity Profile	No need of specific recycling operations
Contractual warranty	
Warranty	18 months