

# Product data sheet

## Characteristics

# 8903SQA11V02

lighting contactor, mechanically held, 100A, 3 pole, NEMA 12, 120/110V 60/50Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



## Main

Product	Mechanically Held Lighting Contactor
Type	S

## Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	100 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	31.50 in (800 mm)
Depth	9.25 in (235 mm)
Width	18.15 in (461 mm)

## Environment

Enclosure Type	NEMA 12/3R painted sheet steel surface none
Product certifications	UL listed CSA

## Ordering and shipping details

Category	21324 - 8903 S (NOT S*C) MECH.
Discount Schedule	CP1
GTIN	00785901780199
Package weight(Lbs)	4.42 kg (9.75 lb(US))
Returnability	No
Country of origin	MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

Contractual warranty

Warranty	18 months
----------	-----------