# Product data sheet Characteristics

# MG26925

Multi 9 accy, aux switch, 20 A, 120/240 V, 1 pole, 10 kA, DIN rail



Product availability: Non-Stock - Not normally stocked in distribution facility



#### Main

Range	Multi 9
Line Rated Current	20 A

## Complementary

System Voltage	120/240 V	
	277 V	
	65 V	
Poles description	1P	
Interrupt Rating	10 KA	
	5 kA	
Mounting support	DIN rail	

#### Environment

Product certifications	IEC
	UL listed

### Ordering and shipping details

eraeinig arra emppring actains	
Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901892175
Package weight(Lbs)	0.04 kg (0.09 lb(US))
Returnability	No
Country of origin	BE

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Contractual warranty	