## Product data sheet Characteristics

### 9998LH45

# Replacement coil, 120VAC 50Hz, 8903L Contactor, 8-12 poles

Product availability: Non-Stock - Not normally stocked in distribution facility



#### Main

Product or component type	Coil	
Accessory / separate part destination	Class 8903 contactor	

Complementary

[Ue] rated operational voltage       120 V AC 50 Hz         Inrush power in VA       170 VA         Average consumption       35 VA         Height       2.38 in (60.5 mm)         Width       2.11 in (53.6 mm)         Depth       1.46 in (37.1 mm)		
Average consumption         35 VA           Height         2.38 in (60.5 mm)           Width         2.11 in (53.6 mm)	[Ue] rated operational voltage	120 V AC 50 Hz
Height 2.38 in (60.5 mm)  Width 2.11 in (53.6 mm)	Inrush power in VA	170 VA
Width 2.11 in (53.6 mm)	Average consumption	35 VA
The state of the s	Height	2.38 in (60.5 mm)
Depth 1.46 in (37.1 mm)	Width	2.11 in (53.6 mm)
	Depth	1.46 in (37.1 mm)

#### Ordering and shipping details

Discount Schedule CP10	
Dissourit Confedure Of To	
GTIN 00785901284659	
Package weight(Lbs) 0.02 kg (0.04 lb(US))	
Returnability No	
Country of origin MX	

#### Offer Sustainability

EU RoHS Directive	Compliant EPEU RoHS Declaration	
China RoHS Regulation	☐ China RoHS Declaration	

#### Contractual warranty

Contractual warranty		
Warranty	18 months	