

Product data sheet

Characteristics

8903S QO11V08

lighting contactor, mechanically held, 100 A, 3 pole, open, 208V 60Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Product	Mechanically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	208 V AC 60 Hz
Current Rating	100 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Without
Other Options	None
Electrical connection	Lugs
Height	7.24 in (184 mm)
Depth	6.73 in (171 mm)
Width	5.94 in (151 mm)

Environment

Enclosure Type	Not rated (open device) surface none
Product certifications	UL listed CSA

Ordering and shipping details

Category	21324 - 8903 S (NOT S°C) MECH.
Discount Schedule	CP1
GTIN	00785901851493
Package weight(Lbs)	6.06 kg (13.35 lb(US))
Returnability	No
Country of origin	MX

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di(2-ethylhexyl)phthalate (DEHP) which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------