

Product availability: Non-Stock - Not normally stocked in distribution facility



### Main

|                           |                                    |
|---------------------------|------------------------------------|
| Device short name         | EGX300                             |
| Product or component type | Gateway module                     |
| Device application        | Gateway Server                     |
| Range compatibility       | Masterpact<br>Compact<br>PowerPact |

### Complementary

|                            |  |
|----------------------------|--|
| Communication network type | RS232/485, Modbus RTU and ASCII even/odd or none 38400/57600 bauds SUB-D 9<br>RS232/485, PowerLogic (SY/MAX) even/odd or none 38400/57600 bauds SUB-D 9<br>RS232/485, JBUS even/odd or none 38400/57600 bauds SUB-D 9<br>Ethernet, HTTP RJ45<br>Ethernet, Modbus TCP/IP RJ45<br>Ethernet, FTP RJ45<br>Ethernet, SNMP RJ45<br>Ethernet, BOOTP (Bootstrap Protocol) RJ45 |
| Communication gateway      | Ethernet/fieldbus  |
| Web server                 | Embedded   |
| Mounting mode              | By clips   |
| Mounting support           | 35 mm DIN rail   |
| Control type               | By software  |
| [Us] rated supply voltage  | 24 V DC  |
| Power consumption in W     | 4 W  |
| Product certifications     | UL 508<br>FCC Class A<br>CUL   |
| Standards                  | EN 61000-4-2<br>EN 61000-4-5<br>EN 61000-6-2<br>UL 60950<br>EN 61000-4-3<br>EN 61000-4-8<br>EN/IEC 60950<br>EN 61000-4-6<br>EN 55011<br>EN 55022<br>EN 61000-4-4   |
| Height                     | 3.18 in (80.8 mm)  |
| Width                      | 2.83 in (72 mm)  |
| Depth                      | 2.59 in (65.8 mm)  |
| Product weight             | 0.37 lb(US) (0.17 kg)  |
| Language                   | English<br>Italian<br>Spanish<br>Chinese<br>German<br>French   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |  |
|---------------------------------------|--|
| IP degree of protection               | IP30   |
| Relative humidity                     | 5...95 % 131 °F (55 °C) without condensation |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                   |

## Ordering and shipping details

|                     |                                  |
|---------------------|----------------------------------|
| Category            | 09785 - POWERLOGIC SYSTEM CMPNTS |
| Discount Schedule   | PL1                              |
| GTIN                | 00785901673262                   |
| Package weight(Lbs) | 0.34 kg (0.74 lb(US))            |
| Returnability       | No                               |
| Country of origin   | IN                               |

## Offer Sustainability

|                          |  |
|--------------------------|--|
| Sustainable offer status | Green Premium product  |
| EU RoHS Directive        | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile      | <a href="#">End Of Life Information</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|