



### Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

### Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	135 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Solid state Motor Logic class 10/20
Electrical connection	Screw clamp terminals
NEMA size	4
Maximum Height	25.16 in (639 mm)
Maximum Depth	9.02 in (229 mm)
Maximum Width	11.26 in (286 mm)

### Environment

Enclosure Type	NEMA 1 painted sheet steel
Product certifications	NEMA CSA UL Listed

### Ordering and shipping details

Category	21193 - 8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	45.72 lb(US) (20.74 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Not compliant
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>