

## Product data sheet

### Characteristics

# 2510MBW1

Manual Starter, integral horsepower, NEMA M0, 600 VAC, 2 pole, 2 HP at 230 VAC, single phase, no indicator, NEMA 4/4X



### Main

|           |                |
|-----------|----------------|
| Product   | Manual Starter |
| Type      | M              |
| NEMA Size | M-0            |

### Complementary

|                                  |                                                  |
|----------------------------------|--------------------------------------------------|
| Control Unit                     | Push-button                                      |
| Pilot Light                      | No indicator                                     |
| Horsepower Rating                | 1 Hp 115 V AC, 1 phase<br>2 hp 230 V AC, 1 phase |
| Voltage Rating                   | 600 V AC                                         |
| Number of Poles                  | 2P                                               |
| Starter Type                     | Non reversing                                    |
| Electrical Connection            | Pressure wire clamp                              |
| Overload Relay Type              | Melting alloy                                    |
| Number of Thermal Units Required | 1                                                |
| Wire Gauge                       | AWG 14...AWG 8 copper                            |
| Auxiliary Contacts               | Without                                          |
| Maximum Height                   | 10.34 in (262.64 mm)                             |
| Maximum Width                    | 5.13 in (130.30 mm)                              |
| Maximum Depth                    | 5.78 in (146.81 mm)                              |

### Environment

|                       |                                                             |
|-----------------------|-------------------------------------------------------------|
| Certifications        | CSA LR60905 class 3211 05<br>UL listed file E42243 CCN NLRV |
| NEMA Enclosure Rating | NEMA 4/4X glass polyester                                   |

### Ordering and shipping details

|                     |                            |
|---------------------|----------------------------|
| Category            | 21103 - 2510,2511,2512 M,T |
| Discount Schedule   | CP1                        |
| GTIN                | 00785901820819             |
| Package weight(Lbs) | 5.67 lb(US) (2.57 kg)      |
| Returnability       | No                         |
| Country of origin   | MX                         |

Offer Sustainability

|                            |                                               |
|----------------------------|-----------------------------------------------|
| REACH Regulation           | <a href="#">REACH Declaration</a>             |
| REACH free of SVHC         | Yes                                           |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                           |
| RoHS exemption information | <a href="#">Yes</a>                           |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>        |

Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|