# 9013GSG2J21H PRESSURE SWITCH 575VAC 2HP G +OPTIONS

Main	
Device short name	G
Enclosure type	Standard environment enclosure indoor
Product specific application	Control electrically driven water pumps and air compressors

Square D Pumptrol

Standard

	Comp	lementary
--	------	-----------

Complementary	
Adjustable range on rising pressure	2080 psi (137.90551.58 kPa)
Approximate adjustable differential	1530 psi (103.42206.84 kPa)
Maximum Depth	3.68 in (93.47 mm)
Electrical connection	Screw clamp terminal
Fixing mode	By brackets
Fluid connection type	0.25 inch NPSF internal
Maximum Height	5.72 in (145.29 mm)
Material	Zinc plated steel flange
Materials in contact with fluid	Nitrile (Buna-N) diaphragm
Maximum pressure	300 psig
Maximum Horse Power Rating	2 Hp 230 V AC, 1 phase 1 Hp 115 V AC, 1 phase 2 hp 460/575 V AC, 1 phase
Number of poles	2
Permissible voltage	575 V AC
Pressure actuator	Diaphragm
Pressure setting range	206.84344.74 kPa (3050 psi)
Net Weight	2.25 lb(US) (1.02 kg)
Range on decreasing pressure	560 psi (34.47413.69 kPa)
Scale type	Adjustable differential
Switch function	DPDT
Maximum Width	3.44 in (87.38 mm)

Range of product

Switch application

#### Environment

NEMA degree of protection	NEMA 1
Product certifications	CSA file LR25490 UL listed file E12158 CCN NKPZ

### Ordering and shipping details

21536 - 9013 G COMMERCIAL PRESSURE SWITCH
CP7G
00785901284246
2 lb(US) (0.91 kg)
No
MX

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not applicable, out of EU RoHS legal scope
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☐ End Of Life Information
	End Of Life Information

### Contractual warranty

	•
Warranty	18 months