



Main

Range	AccuSine
Product or component type	Rectangular Current Transformer
Accessory / separate part category	Measurement accessory
Range compatibility	AccuSine PCS+ active harmonic filter AccuSine PFV+ electronic VAR controller
Current transformer type	Split core balance
Secondary current	1 A

Complementary

Current transformer ratio	1500/1
Electrical connection	Flying lead 11.98 ft (3.65 m) 720 V
Input impedance	15 Ohm
Line Rated Current	1500 A
Thermal factor	1.25 86 °F (30 °C) 1 131 °F (55 °C)
Network frequency	50...400 Hz
Measurement accuracy	1 %
Accuracy class	Class 1
[Ue] rated operational voltage	< 720 V AC 50...400 Hz
[Uimp] rated impulse withstand voltage	10 kV 50 µs)
Width	Outside 5.50 in (139.7 mm) Inner 2.75 in (69.8 mm)
Height	Outside 9.37 in (238 mm) Inner 6.62 in (168.2 mm)
Depth	Outside 1.50 in (38.1 mm)
Net Weight	4.19 lb(US) (1.9 kg)

Environment

Standards	IEC 60044-1
Product certifications	CURus CE
Ambient air temperature for operation	-49...131 °F (-45...55 °C)

Ordering and shipping details

Category	00089 - ACTIVE FILTERS
Discount Schedule	DE2C
GTIN	03606480891786
Nbr. of units in pkg.	1
Package weight(Lbs)	4.41 lb(US) (2.00 kg)
Returnability	No
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.