



Main

| | |
|-----------------------------|--|
| Range of product | Harmony XALK |
| Product or component type | Complete control station |
| Device short name | XALK |
| Product destination | For XB5 Ø 22 mm control and signalling units |
| Control station application | Emergency switching off function |
| Colour of base of enclosure | Light grey RAL 7035) |
| Colour of cover | Yellow RAL 1021) |

Environment

| | |
|---------------------------------------|----------------------------|
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| IP degree of protection | IP66 |
| NEMA degree of protection | NEMA 13 |

Ordering and shipping details

| | |
|-----------------------|-----------------------|
| Category | 22475 - WALL STATIONS |
| Discount Schedule | CS2 |
| GTIN | 00785901680666 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 1.17 lb(US) (0.53 kg) |
| Returnability | No |
| Country of origin | MX |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.