

792XDX3C-12A

Power relay, Legacy, 4PDT, 3A, 12 VAC, low level bifurcated contacts, clear cover



Main

Product range	Legacy
Product type	Relay
Switch function	4PDT
Contact composition	4 NO + 4 NC

Complementary

Input current	3 A
Contacts material	Gold plated bifurcated silver
Local signalling	Flag
Minimum switching current	3 mA 5 V
Coil Resistance	44 Ohm
Input voltage	12 V AC
Drop-out voltage threshold	$\geq 0.15 U_c$ AC $\geq 0.1 U_c$ DC
[Ie] rated operational current	3 A 240/277 V AC UL 3 A 120 V AC UL 3 A 30 V DC UL 2 A AC-1 NO)IEC 2 A DC-1 NO)IEC 1 A AC-1 NC)IEC 1 A DC-1 NC)IEC
Average coil consumption in VA	0.9 AC 60 Hz
Voltage range	0.8...1.1 U_n AC/DC
Maximum switching voltage	300 V UL 300 V CSA 250 V IEC
Maximum Horse Power Rating	0.0625 hp 120 V AC
Connections - terminals	Faston connectors
Mounting	Panel DIN rail
Height	1.37 in (34.8 mm)
Width	0.83 in (21 mm)
Depth	1.07 in (27.2 mm)
Net Weight	1.31 oz (37 g)
Operating time	25 ms 20 ms at maximum rated voltage

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

Ambient temperature range - operational	-40...131 °F (-40...55 °C)
Ambient air temperature for storage	-40...185 °F (-40...85 °C)
Product certifications	UL CSA CE
Electrical durability	100000 cycles resistive
Mechanical durability	10000000 cycles
Dielectric strength	2000 V AC between coil and contact 2000 V AC between poles 1300 V AC between contacts
Shock resistance	10 gn in operation 30 gn not operating
Vibration resistance	3 gn 35...150 Hz)operating +/- 1 mm 10...35 Hz)operating 5 gn 35...150 Hz)not operating +/- 1 mm 10...35 Hz)not operating
Surge withstand duration	1.2/50 µs

Ordering and shipping details

GTIN	03606480781605
------	----------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.