

### Main

Product or component type	Industrial Control Transformer
Type	T

### Complementary

Number of Phases	1 phase
Power Rating	5000 VA UL 5000 VA CSA 5000 VA NOM 3000 VA
Primary to Secondary Voltage	440 V 220 V 460 V 230 V 480 V 240 V
Temperature rise	115 °C
Electrical connection	Screw clamp terminals
Maximum Height	8.46 in (214.88 mm)
Maximum Width	9 in (228.60 mm)
Maximum Depth	8.73 in (221.74 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC2

### Environment

Product certifications	CSA file LR37055 guide 184-N-90 UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation temperature	356 °F (180 °C)

### Ordering and shipping details

Category	16205 - 9070 T (NOT TF) 3000 - 5000VA
Discount Schedule	CP8
GTIN	00785901339618
Nbr. of units in pkg.	1
Package weight(Lbs)	93.5 lb(US) (42.41 kg)
Returnability	No
Country of origin	US

### Packing Units

Package 1 Height	13.20 in (33.528 cm)
Package 1 width	11.80 in (29.972 cm)
Package 1 Length	14.80 in (37.592 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------