



### Main

Product	Switched fuse mechanism
Not Included	Fuse to be ordered separately

### Complementary

Protection type	Fuse boric acid
Associated fuse rating	10 A E 15 A E 20 A E 25 A E 30 A E 40 A E 50 A E 65 A E 80 A E 100 A E 125 A E 150 A E 175 A E 200 A E 250 A E 300 A E 400 A E
Line Rated Current	600 A
Momentary Amperes Asymmetrical	40 kA
Frequency	50/60 Hz
Number of Poles	3P
[Ur] highest voltage for equipment	15 kV
Basic Insulation Level	90 kV
Enclosure Rating	NEMA 1
Electrical connection	Lugs
Type of installation	Indoor
Wire Gauge	AWG 2...600 kcmil aluminium/copper
Enclosure Width	965.20 mm (38 in)
Enclosure Depth	1384.30 mm (54.5 in)
Enclosure Height	2286.00 mm (90 in)

### Environment

Product certifications	CUL UL Listed
------------------------	------------------

Ordering and shipping details

Category	07944-15KV N1 DIGEST HVL
Discount Schedule	PE5A
Package weight(Lbs)	1200.00 lb(US) (544.311 kg)
Returnability	Yes
Country of origin	US

Contractual warranty

Warranty	18 months
----------	-----------