



## Main

|                           |                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                     | Multi 9                                                                                                                                                                                                                                                                                                                                                    |
| Product name              | Multi 9 C60                                                                                                                                                                                                                                                                                                                                                |
| Product or component type | Miniature circuit-breaker                                                                                                                                                                                                                                                                                                                                  |
| Device short name         | C60BPR                                                                                                                                                                                                                                                                                                                                                     |
| Device application        | Distribution                                                                                                                                                                                                                                                                                                                                               |
| Poles description         | 3P                                                                                                                                                                                                                                                                                                                                                         |
| Number of protected poles | 3                                                                                                                                                                                                                                                                                                                                                          |
| Line Rated Current        | 15 A 77 °F (25 °C) EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                          |
| Network type              | AC                                                                                                                                                                                                                                                                                                                                                         |
| Trip unit technology      | Thermal-magnetic                                                                                                                                                                                                                                                                                                                                           |
| Curve code                | D                                                                                                                                                                                                                                                                                                                                                          |
| Breaking capacity         | 6 KA Icu 440 V AC EN/IEC 60947-2<br>10 KA Icu 415 V AC EN/IEC 60947-2<br>20 KA Icu 240 V AC EN/IEC 60947-2<br>6 KA Icu 440 V AC GB 14048.2<br>10 KA Icu 415 V AC GB 14048.2<br>20 KA Icu 240 V AC GB 14048.2<br>14 KA AIR 240 V AC UL 489<br>10 KA AIR 480Y/277 V AC UL 489<br>14 KA AIR 240 V AC CSA C22.2 No 5<br>10 KA AIR 480Y/277 V AC CSA C22.2 No 5 |
| Suitability for isolation | Yes EN/IEC 60947-2                                                                                                                                                                                                                                                                                                                                         |
| Standards                 | EN/IEC 60947-2<br>GB 14048.2<br>UL 489<br>CSA C22.2 No 5                                                                                                                                                                                                                                                                                                   |
| Product certifications    | IEC<br>CCC<br>CSA<br>UL                                                                                                                                                                                                                                                                                                                                    |

## Complementary

|                                        |                                                                                                                                                                                                                                      |
|----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [Ue] rated operational voltage         | 240 V AC 50/60 Hz<br>415 V AC 50/60 Hz<br>440 V AC 50/60 Hz                                                                                                                                                                          |
| Magnetic tripping limit                | 12 x In +/- 20 % AC                                                                                                                                                                                                                  |
| [Ics] rated service breaking capacity  | 4.5 KA 75 % EN/IEC 60947-2 - 440 V AC<br>7.5 KA 75 % EN/IEC 60947-2 - 415 V AC<br>15 KA 75 % EN/IEC 60947-2 - 240 V AC<br>4.5 KA 75 % GB 14048.2 - 440 V AC<br>7.5 KA 75 % GB 14048.2 - 415 V AC<br>15 KA 75 % GB 14048.2 - 240 V AC |
| [Ui] rated insulation voltage          | 500 V AC EN/IEC 60947-2                                                                                                                                                                                                              |
| [Uimp] rated impulse withstand voltage | 6 kV EN/IEC 60947-2                                                                                                                                                                                                                  |
| Contact position indicator             | Yes                                                                                                                                                                                                                                  |
| Control type                           | Toggle                                                                                                                                                                                                                               |
| Local signalling                       | ON/OFF indication                                                                                                                                                                                                                    |
| Mounting mode                          | Clip-on                                                                                                                                                                                                                              |
| Mounting support                       | DIN rail                                                                                                                                                                                                                             |
| 9 mm pitches                           | 6                                                                                                                                                                                                                                    |
| Maximum Height                         | 5.00 in (127 mm)                                                                                                                                                                                                                     |

|                          |                                    |
|--------------------------|------------------------------------|
| Maximum Width            | 2.13 in (54 mm)                    |
| Maximum Depth            | 2.83 in (72 mm)                    |
| Color                    | Gray                               |
| Mechanical durability    | 20000 cycles                       |
| Electrical durability    | 10000 cycles                       |
| Provision for padlocking | Padlockable                        |
| Connections - terminals  | Ring terminal top or bottom)       |
| Tightening torque        | 17.70 lbf.in (2 N.m) top or bottom |
| Earth-leakage protection | Without                            |

## Environment

|                                       |                                                   |
|---------------------------------------|---------------------------------------------------|
| IP degree of protection               | IP20IEC 60529<br>IP40 modular enclosure)IEC 60529 |
| Pollution degree                      | 3 EN/IEC 60947-2                                  |
| Tropicalisation                       | 2 IEC 60068-1                                     |
| Relative humidity                     | 95 % 131 °F (55 °C)                               |
| Operating altitude                    | 0...6561.68 ft (0...2000 m)                       |
| Ambient air temperature for operation | -22...158 °F (-30...70 °C)                        |
| Ambient air temperature for storage   | -40...176 °F (-40...80 °C)                        |

## Ordering and shipping details

|                       |                           |
|-----------------------|---------------------------|
| Category              | 00949 - M9 GEN 2 CB UL489 |
| Discount Schedule     | DE2                       |
| GTIN                  | 00785901136187            |
| Nbr. of units in pkg. | 1                         |
| Package weight(Lbs)   | 0.95 lb(US) (0.43 kg)     |
| Returnability         | Yes                       |
| Country of origin     | FR                        |

## Packing Units

|                              |                          |
|------------------------------|--------------------------|
| Unit Type of Package 1       | PCE                      |
| Package 1 Height             | 2.13 in (5.4 cm)         |
| Package 1 width              | 2.95 in (7.5 cm)         |
| Package 1 Length             | 5.00 in (12.7 cm)        |
| Unit Type of Package 2       | BB1                      |
| Number of Units in Package 2 | 4                        |
| Package 2 Weight             | 3.97 lb(US) (1.803 kg)   |
| Package 2 Height             | 8.66 in (22 cm)          |
| Package 2 width              | 3.15 in (8 cm)           |
| Package 2 Length             | 5.12 in (13 cm)          |
| Unit Type of Package 3       | S03                      |
| Number of Units in Package 3 | 32                       |
| Package 3 Weight             | 32.87 lb(US) (14.911 kg) |
| Package 3 Height             | 11.81 in (30 cm)         |
| Package 3 width              | 11.81 in (30 cm)         |
| Package 3 Length             | 15.75 in (40 cm)         |

## Offer Sustainability

|                            |                                                                                                                                   |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                             |
| EU RoHS Directive          | Compliant  <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes                                                                                                                               |
| RoHS exemption information |  Yes                                           |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>        |

|                          |                                                                                                                                |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Environmental Disclosure |  <a href="#">Product Environmental Profile</a> |
| WEEE                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.   |