

### Main

Range	PowerLogic
Product name	PowerLogic ENERGY METER
Product or component type	Energy meter
Device application	Energy monitoring

### Complementary

Type of measurement	Energy consumption Power Peak demand power Reactive power Power factor Voltage Current
Measurement accuracy	+/- 1 %
Measurement voltage	120 V AC between phase and neutral 240 V AC between phases
[Us] rated supply voltage	120 V AC - 25...10 %
Network frequency	50 Hz 60 Hz
Line Rated Current	400 A
Display type	Backlit LCD
Display size	1.2 x 3.8 inch
Information displayed	Energy consumption Power Power maximum) Reactive power Power factor Voltage Current
Sampling rate	1280 Hz
Provided equipment	3 x current transformer
CT size	2.45 x 2.89 inch
Standards	ANSI C12.1
Product certifications	UL UL 3111-1 CUL
Maximum Width	7.60 in (193 mm)
Depth	Meter 2.99 in (76 mm)
Maximum Height	8.31 in (211 mm)

### Environment

Isolation voltage	, 2500 V
Relative humidity	0...95 % non-condensing
Ambient air temperature for operation	32...122 °F (0...50 °C)
Ambient air temperature for storage	-40...158 °F (-40...70 °C)

## Ordering and shipping details

Category	09779 - POWERLOGIC ENERGY METER
Discount Schedule	PL1
GTIN	00785901564379
Package weight(Lbs)	6 lb(US) (2.72 kg)
Returnability	No
Country of origin	US

## Offer Sustainability

EU RoHS Directive	Not compliant
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------