## Product data sheet Characteristics

# DL1BKG4 Flashing LED, 120 Vac Red





#### Main

Range compatibility	Harmony XVB Harmony XVP Harmony XVD
Accessory / separate part designation	Protected LED bulb
Accessory / separate part type	LED bulb
Accessory / separate part category	Lighting accessories
Accessory / separate part destination	Beacon and indicator bank
[Us] rated supply voltage	120 V AC
Signalling type	Flashing
Signalling colour	Red
Sale per indivisible quantity	1

#### Complementary

Current consumption	17 mA
Bulb base	BA 15d
Net Weight	0.03 lb(US) (0.015 kg)

#### Ordering and shipping details

ordoning and ompping dotailo	
Category	22611 - XVB-STACKLIGHTS
Discount Schedule	XV
GTIN	00785901967620
Nbr. of units in pkg.	1
Package weight(Lbs)	0.03 lb(US) (0.01 kg)
Returnability	Yes
Country of origin	ID

#### **Packing Units**

Unit Type of Package 1	PCE	
Package 1 Height	1.38 in (3.5 cm)	
Package 1 width	1.77 in (4.5 cm)	
Package 1 Length	2.36 in (6 cm)	
Unit Type of Package 2	S01	
Number of Units in Package 2	60	
Package 2 Weight	33.51 oz (950 g)	
Package 2 Height	5.91 in (15 cm)	
Package 2 width	5.91 in (15 cm)	
Package 2 Length	15.75 in (40 cm)	

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lea compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

#### Contractual warranty

14/	10 "
vvarrantv	18 months
	To monding