



### Main

Range	TeSys
Product name	TeSys LK
Product or component type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

### Complementary

Poles description	3P
Network type	AC
Network frequency	50/60 Hz
[Ie] rated operational current	800 A400 V AC AC-22A IEC 800 A400 V AC AC-23A IEC 630 A690 V AC AC-22A IEC 400 A690 V AC AC-23A IEC 800 A CSA 800 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] rated insulation voltage	1000 V
Control type	Rotary handle
Type of operating handle	External right side External frontal
Mounting support	Plate
[Uimp] rated impulse withstand voltage	12 kV IEC
Rated power in W	450 KW 400 V 560 KW 500 V 400 kW 690 V
Rated power in hp	200 Hp 240 V 480 A AC 500 Hp 480 V 477 A AC 500 hp 600 V 336 A AC
[Icw] rated short-time withstand current	75 kA
Mechanical durability	3500 cycles
Electrical durability	500 cycles
Connections - terminals	Lugs-ring terminals 2 0.05 in <sup>2</sup> (34 mm <sup>2</sup> ) Bars 2 40 x 5 mm
Maximum Height	12.60 in (320 mm)
Maximum Width	14.57 in (370 mm)
Maximum Depth	5.51 in (140 mm)

### Environment

Standards	CSA C22.2 No 4 IEC 60947-3 UL98
Product certifications	CE CSA UL

## Ordering and shipping details

Category	22640 - IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	00785901546887
Nbr. of units in pkg.	1
Package weight(Lbs)	26.86 lb(US) (12.18 kg)
Returnability	No
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.63 in (27 cm)
Package 1 width	15.94 in (40.5 cm)
Package 1 Length	20.87 in (53 cm)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide which is known to the State of California to cause Carcinogen harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------