



## Main

Range	9422T
Product	Disconnect Switch
Disconnect Type	Fusible disconnect switch

## Complementary

Mounting Type	Flange rod variable depth
Current Rating	60 A
Horsepower Rating	15 Hp 200 V AC 15 Hp 230 V AC 30 Hp 460 V AC 50 Hp 575 V AC 10 hp 250 V DC
Fuse Rating	60 A 600 V
Handle Type	6 in handle included NEMA 1/3/3R/4 enclosures sheet steel
Fuse Type	J R H K

## Environment

Certifications	UL Recognized CSA
----------------	----------------------




## Ordering and shipping details

Category	21732 - 9422
Discount Schedule	CP1
GTIN	00785901872191
Nbr. of units in pkg.	1
Package weight(Lbs)	9.05 lb(US) (4.11 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.10 in (18.034 cm)
Package 1 width	11.20 in (28.448 cm)
Package 1 Length	16.00 in (40.64 cm)

Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------