



### Main

|                                 |                                  |
|---------------------------------|----------------------------------|
| Range of product                | Harmony 9001K                    |
| Product or component type       | Complete illuminated push-button |
| Device short name               | 9001K                            |
| Bezel material                  | Chromium plated metal            |
| Mounting diameter               | 1.18 in (30 mm)                  |
| Operator additional information | Full guard in plastic            |
| Light source                    | incandescent                     |

### Complementary

|                              |                        |
|------------------------------|------------------------|
| Shape of signaling unit head | Round                  |
| Type of operator             | Spring return          |
| Operator profile             | Flush, unmarked        |
| Bulb base                    | BA 9s                  |
| Light block supply           | Direct 6 V AC/DC       |
| Mechanical durability        | 5000000 cycles         |
| Operating position           | Any position           |
| Net Weight                   | 0.37 lb(US) (0.166 kg) |

### Environment

|                                       |                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Standards                             | CSA C22.2 No 14<br>JIS C 4520<br>EN/IEC 60947-5-4<br>JIS C 852<br>EN/IEC 60947-5-1<br>UL 508<br>EN/IEC 60947-1 |
| Product certifications                | UL 508<br>NEMA                                                                                                 |
| Protective treatment                  | TC                                                                                                             |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)                                                                                     |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                                                     |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6                                                                                  |
| Shock resistance                      | 50 gn IEC 60068-2-27                                                                                           |
| Electrical shock protection class     | Class II IEC 61140                                                                                             |
| IP degree of protection               | IP66 IEC 60529                                                                                                 |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4                                          |

## Ordering and shipping details

|                       |                               |
|-----------------------|-------------------------------|
| Category              | 21426 - 9001 K (NOT KA,KM,KX) |
| Discount Schedule     | CS1                           |
| GTIN                  | 00785901932123                |
| Nbr. of units in pkg. | 1                             |
| Package weight(Lbs)   | 0.5 lb(US) (0.23 kg)          |
| Returnability         | No                            |
| Country of origin     | MX                            |

## Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 6.35 in (16.129 cm)  |
| Package 1 width  | 2.50 in (6.350 cm)   |
| Package 1 Length | 16.13 in (40.968 cm) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                 |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                        |
| Mercury free               | Yes                                                                                                                                                                                                                                                                   |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                         |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                          |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|