

70-782EL8-1

Socket, Legacy general purpose relay accessory, DPDT, 12A, 300 V, 8 pins, lift terminals, locking plastic clip, 782 s



Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 792XBX Diode 70-BSMD Signalling device 70-BSMLG Suppressor module 70-BSMM Jumper wire 16-782CBJ-1
Number of terminals	8
Switch function	DPDT
Contact composition	2 NO + 2 NC

Complementary

Line Rated Current	12 A
Rated voltage	300 V
Contact terminal arrangement	Separate
Connections - terminals	Lift terminals solid Lift terminals stranded
Tightening torque	Chassis 0.8 N.m, AWG 14...AWG 12, copper Screw 1 N.m
Fixing mode	By screw M3.5, M3.5 panel Clip-on 35 mm symmetrical DIN rail
Shape of screw head	Combination roundhead
Net Weight	1.62 oz (46 g)
Width	1.06 in (26.9 mm)
Depth	3.11 in (79 mm)

Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
IP degree of protection	IP20
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

Ordering and shipping details

GTIN	03606480278150
------	----------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.