



## Main

|                           |                   |
|---------------------------|-------------------|
| Range of product          | Harmony 9001SK    |
| Product or component type | Pilot light       |
| Device short name         | 9001SK            |
| Lens type                 | Domed plastic     |
| Light block supply        | Direct 12 V AC/DC |

## Complementary

|                                             |                                                              |
|---------------------------------------------|--------------------------------------------------------------|
| Bezel material                              | Plastic                                                      |
| Mounting diameter                           | 1.18 in (30 mm)                                              |
| Shape of signaling unit head                | Round                                                        |
| Cap/operator or lens colour                 | Blue                                                         |
| Light source                                | incandescent                                                 |
| Bulb base                                   | BA 9s                                                        |
| [Us] rated supply voltage                   | 12...14 V AC/DC                                              |
| Tightening torque                           | 7.08 lbf.in (0.8 N.m) EN/IEC 60947-1                         |
| Shape of screw head                         | Cross slotted                                                |
| Connections - terminals                     | Screw clamp terminals, 1 x 0.22...2 x 1.5 mm² EN/IEC 60947-1 |
| [Ith] conventional free air thermal current | 10 A                                                         |
| Short-circuit protection                    | 10 A cartridge fuse EN/IEC 60947-5-1                         |
| [Ui] rated insulation voltage               | 250 V 2)EN/IEC 60947-1                                       |
| [Uimp] rated impulse withstand voltage      | 2.5 kV EN/IEC 60947-1                                        |
| Operating position                          | Any position                                                 |
| CAD overall width                           | 2.13 in (54 mm)                                              |
| CAD overall height                          | 2.76 in (70 mm)                                              |
| CAD overall depth                           | 1.65 in (42 mm)                                              |
| Net Weight                                  | 0.18 lb(US) (0.082 kg)                                       |
| Device presentation                         | Complete product                                             |

## Environment

|                                       |                                                                                  |
|---------------------------------------|----------------------------------------------------------------------------------|
| Electrical shock protection class     | Class II IEC 61140                                                               |
| Protective treatment                  | TC                                                                               |
| IP degree of protection               | IP66 IEC 60529                                                                   |
| NEMA degree of protection             | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4<br>NEMA 4X |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6                                                    |
| Shock resistance                      | 50 gn IEC 60068-2-27                                                             |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C)                                                       |

|                                     |                                                                                                                                  |
|-------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Ambient air temperature for storage | -40...158 °F (-40...70 °C)                                                                                                       |
| Standards                           | CSA C22.2 No 14<br>JIS C8201-5-1<br>UL 508<br>JIS C 852<br>EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>EN/IEC 60947-5-4<br>JIS C8201-1 |
| Product certifications              | NEMA<br>UL 508                                                                                                                   |

## Ordering and shipping details

|                       |                      |
|-----------------------|----------------------|
| Category              | 21429 - 9001 SK,SKY  |
| Discount Schedule     | CS1                  |
| GTIN                  | 03389118037618       |
| Nbr. of units in pkg. | 1                    |
| Package weight(Lbs)   | 0.5 lb(US) (0.23 kg) |
| Returnability         | No                   |
| Country of origin     | MX                   |

## Packing Units

|                        |                    |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE                |
| Package 1 Height       | 1.80 in (4.572 cm) |
| Package 1 width        | 2.10 in (5.334 cm) |
| Package 1 Length       | 3.60 in (9.144 cm) |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                       |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status   | Green Premium product                                                                                                                                                                                                                                                 |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
| REACH free of SVHC         | Yes                                                                                                                                                                                                                                                                   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                                                                                                                                                                        |
| Toxic heavy metal free     | Yes                                                                                                                                                                                                                                                                   |
| Mercury free               | Yes                                                                                                                                                                                                                                                                   |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                                                                                                                                                                         |
| Circularity Profile        | <a href="#">End Of Life Information</a>                                                                                                                                                                                                                               |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                          |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Dimensions



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.