

# Product data sheet

## Characteristics

# XVCTL1

Monolithic tower light, red-orange-green, 40mm, base mounting, steady or flashing, with buzzer 70...85 dB, IP23, 24 V AC DC



### Main

|                                    |   |
|------------------------------------|---|
| Product or component type          | Complete pre-wired monolithic tower light   |
| Beacon or indicator bank unit type | 3 illuminated units   |
| Sound signalling                   | Buzzer  |
| Mounting diameter                  | 1.57 in (40 mm)   |
| Device short name                  | XVC   |
| Light source                       | LED steady or flashing red<br>LED steady or flashing orange<br>LED steady or flashing green |
| Supply circuit type                | AC/DC   |

### Complementary

|  |  |
|--|--|
| Material                               | Polycarbonate illuminated unit<br>ABS (acrylonitrile butadiene-styrene) base unit<br>PBT + ABS (UL94-V0) top cover<br>SGP (chromium-plated) support tube |
| Mounting location                      | On support tube, 17 mm   |
| [Us] rated supply voltage              | 24 V   |
| Cable cross section                    | 0.00 In <sup>2</sup> (0.33 mm <sup>2</sup> )<br>0.00 in <sup>2</sup> (0.83 mm <sup>2</sup> )   |
| AWG gauge                              | AWG 22<br>AWG 18   |
| Cable length                           | 17.72 in (450 mm)  |
| Marking                                | CE   |
| [Uimp] rated impulse withstand voltage | 4 kV   |
| Flashing frequency                     | 1 Hz   |

### Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | EN/IEC 60947-1<br>EN/IEC 60947-5-1              |
| Product certifications                | UL  |
| Protective treatment                  | TC  |
| Ambient air temperature for storage   | -31...158 °F (-35...70 °C)                      |
| Ambient air temperature for operation | 14...122 °F (-10...50 °C)                       |
| Overvoltage category                  | Class I EN/IEC 61140                            |
| IP degree of protection               | IP23 vertical surface installation EN/IEC 60529 |

### Ordering and shipping details

|                       |                                      |
|-----------------------|--------------------------------------|
| Category              | 22750 - INDUSTRIAL POINT OF PURCHASE |
| Discount Schedule     | IPOP                                 |
| GTIN                  | 00785901557234                       |
| Nbr. of units in pkg. | 1                                    |
| Package weight(Lbs)   | 0.51 lb(US) (0.23 kg)                |
| Returnability         | Yes                                  |
| Country of origin     | MX                                   |

## Packing Units

|                  |                       |
|------------------|-----------------------|
| Package 1 Height | 22.86 in (58.064 cm)  |
| Package 1 width  | 9.00 in (22.860 cm)   |
| Package 1 Length | 58.06 in (147.484 cm) |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>                               |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | <a href="#">End Of Life Information</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |