



Main

| | |
|---------------------------|--|
| Product or component type | Plug-in unit |
| Range of product | I-Line |
| Circuit breaker type | L-Frame |
| Trip unit technology | Electronic, standard, Micrologic 3.3, LI |

Complementary

| | |
|---|--|
| Protection type | Circuit breaker |
| Mounting mode | Plug-in |
| [Ue] rated operational voltage | 600 V AC |
| Line Rated Current | 400 A |
| Number of Phases | 3 phase |
| Poles description | 3P |
| Interrupt Rating | 65 KA 240 V AC 35 KA 480 V AC 18 kA 600 V AC |
| [Ics] rated service short-circuit breaking capacity | 80 % |
| Wiring configuration | 4-wire (integral ground bus) |
| AWG gauge | AWG 2/0...500 kcmil 2 phase AWG 1/0...600 kcmil 2 neutral AWG 6...300 kcmil 1 ground |
| Maximum Depth | 14.45 in (367 mm) |
| Maximum Height | 17.40 in (442 mm) |
| Maximum Width | 36.46 in (926 mm) |

Environment

| | |
|------------------------|--|
| Product certifications | UL listed file E22182 CSA C22.2 No 27 |
| Standards | UL 857 |

Ordering and shipping details

| | |
|---------------------|---------------------------|
| Category | 20190-PBLI C/B PLUGS |
| Discount Schedule | PE7 |
| Package weight(Lbs) | 121.00 lb(US) (54.885 kg) |
| Returnability | No |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds and Di-isodecyl phthalate (DIDP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Circularity Profile | No need of specific recycling operations |