



Main

| | |
|--------------------|-------------------------------|
| Product | Switched fuse mechanism |
| Application | B |
| Not Included | Fuse to be ordered separately |
| Device application | Transformer right side |

Complementary

| Protection type | Fuse current limiter |
|------------------------------------|--|
| Associated fuse rating | 10 A E 15 A E 20 A E 25 A E 30 A E 40 A E 50 A E 65 A E 80 A E 100 A E 125 A E 150 A E 175 A E 200 A E 250 A E 300 A E 400 A E 350 A E 500 A E |
| Line Rated Current | 600 A |
| Momentary Amperes Asymmetrical | 40 kA |
| Full Load Current | 300 A |
| Frequency | 50/60 Hz |
| Number of Poles | 3P |
| [Ur] highest voltage for equipment | 4.76 kV |
| Basic Insulation Level | 60 kV |
| Enclosure Rating | NEMA 1 |
| Electrical connection | Lugs |
| Wire Gauge | AWG 2...350 kcmil 2 aluminium/copper |
| Service Entry | UG |
| Enclosure Width | 1016.00 mm (40 in) |
| Enclosure Depth | 946.15 mm (37.25 in) |
| Enclosure Height | 2286.00 mm (90 in) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

| | |
|---------------------|-----------------------------|
| Category | 07948-DIGEST HVL/CC |
| Discount Schedule | PE5A |
| Package weight(Lbs) | 1025.00 lb(US) (464.932 kg) |
| Returnability | No |
| Country of origin | US |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|