



Main

| | |
|-------------------|--|
| Bezel material | Chromium plated metal |
| Device short name | K |
| Enclosure type | Dust and oil resistant weatherproof enclosure indoor/outdoor |
| Mounting diameter | 1.18 in (30 mm) |

Complementary

| | |
|-------------------------------|--|
| Line Rated Current | 10 A |
| Cap/operator or lens colour | white |
| Contact operation | Standard fingersafe |
| Light block supply | Full voltage 24 V Full voltage 28 V |
| Operator position information | 3 positions |
| Operator profile | Standard knob |
| Operator profile | 1 projecting push-button |
| Type of operator | Spring return both sides to centre |
| Utilisation category | DC-13 AC-15 |

Environment

| | |
|---------------------------|---|
| NEMA degree of protection | NEMA 1/2/3/3R/4/6/12/13 |
| Product certifications | CE UL listed file E42259 CCN NKCR CSA LR24590 class 3211 03 |

Ordering and shipping details

| | |
|-----------------------|-------------------------------|
| Category | 21426 - 9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.45 lb(US) (0.20 kg) |
| Returnability | No |
| Country of origin | MX |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.