



### Main

Product or component type	Dry Sealed Transformer
Full Capacity Taps	0

### Complementary

Enclosure Code	53X
Phase	1 phase
Primary to Secondary Voltage	240 x 480 V 120/240 V
Power Rating	25 kVA
Temperature rise	115 °C
Maximum Height	24 in (609.60 mm)
Maximum Width	546.10 mm (21.5 in)
Maximum Depth	416.05 mm (16.38 in)
Enclosure mounting	Floor
Enclosure material	Stainless steel

### Environment

Enclosure Type	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product certifications	UL Listed CSA CULus

### Ordering and shipping details

Category	16277 - RESIN LVGP XFMR
Discount Schedule	PE2
Package weight(Lbs)	385 lb(US) (174.63 kg)
Returnability	No

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

RoHS exemption information	 <a href="#">Yes</a>
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations
<b>Contractual warranty</b>	
Warranty	18 months