ZB4BC980

pushbutton head for harsh environment - light blue - without marking





Main

Range of product Harmony XB4 Product or component type Device short name ZB4 Bezel material Chromium plated metal Head type Standard Mounting diameter 0.87 in (22 mm) Sale per indivisible quantity		
type Device short name ZB4 Bezel material Chromium plated metal Head type Standard Mounting diameter 0.87 in (22 mm) Sale per indivisible 1	Range of product	Harmony XB4
Bezel material Chromium plated metal Head type Standard Mounting diameter 0.87 in (22 mm) Sale per indivisible 1	•	Head for push-button
Head type Standard Mounting diameter 0.87 in (22 mm) Sale per indivisible 1	Device short name	ZB4
Mounting diameter 0.87 in (22 mm) Sale per indivisible 1	Bezel material	Chromium plated metal
Sale per indivisible 1	Head type	Standard
'	Mounting diameter	0.87 in (22 mm)
	•	1

Complementary

CAD overall width	1.46 in (37 mm)	
CAD overall height	0.73 in (18.5 mm)	
CAD overall depth	1.46 in (37 mm)	
Net Weight	0.08 lb(US) (0.036 kg)	
Electrical shock protection class	Class I IEC 61140	
Shape of signaling unit head	Round	
Type of operator	Spring return	
Operator profile	Light blue flush, unmarked	
Operator additional information	Vertical mounting Horizontal mounting	
Mechanical durability	10000000 cycles	
Vibration resistance	5 gn 2500 Hz)IEC 60068-2-6	
Shock resistance	30 gn 18 ms) half sine wave acceleration IEC 60068-2-27	
Main group	Harsh environment	
Group of product	Flush unmarked	
Cap/operator or lens colour	Light blue	
Marking	Unmarked	
Electrical composition code	C1 9 single front mounting C2 9 single and double front mounting C11 3 single front mounting C15 1 single front mounting	

Environment

Ambient air temperature for storage	-40185 °F (-4085 °C)	
Ambient air temperature for operation	-40158 °F (-4070 °C)	
IP degree of protection	IP66 IEC 60529 IP69K IP67 IP69	
NEMA degree of protection	NEMA 4 UL 508 NEMA 13 NEMA 12	
Resistance to high pressure washer	0.01 psi (90 Pa) 180 °F (82.5 °C)	
IK degree of protection	IK06 IEC 62262	

Standards	IEC 60947-5-1	
	IEC 60947-1	
	CSA C22.2	
	UL 508	
Product certifications	CSA	
	CE	
	UL	

Ordering and shipping details

Category	22468 - PUSHBUTTONS,22MM(METAL) NEW	
Discount Schedule	CS2	
GTIN	03606480444760	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.07 lb(US) (0.03 kg)	
Returnability	No	
Country of origin	FR	

Packing Units

Package 1 Height	0.376 dm
Package 1 width	0.370 dm
Package 1 Length	0.370 dm

Offer Sustainability

Yes
_
Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Yes
Yes
€Yes
China RoHS Declaration
Product Environmental Profile
End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------