# Product data sheet Characteristics

# XS1N08NA349S

inductive sensor XS1 M8 - L42mm - brass - Sn2.5mm - 12..24VDC - M8





#### Main

Range of product	OsiSense XS
Series name	General purpose
Sensor type	Inductive proximity sensor
Device application	-
Sensor name	XS1
Sensor design	Cylindrical M8
Size	42 mm
Body type	Fixed
Detector flush mounting acceptance	Flush mountable
Material	Metal
Enclosure material	Nickel plated brass
Type of output signal	Discrete
Wiring technique	3-wire
[Sn] nominal sensing distance	0.10 in (2.5 mm)
Discrete output function	1 NO
Output circuit type	DC
Discrete output type	NPN
Electrical connection	Male connector M8, 3 pins
[Us] rated supply voltage	1224 V DC reverse polarity protection
Switching capacity in mA	<= 200 mA DC overload and short-circuit protection
IP degree of protection	IP67 IEC 60529

#### Complementary

Complementary	
Thread type	M8 x 1
Detection face	Frontal
Front material	PPS
Operating zone	0.000.08 in (02 mm)
Differential travel	115% of Sr
Status LED	Output state 1 LED yellow)
Supply voltage limits	1036 V DC
Switching frequency	<= 2500 Hz
Maximum voltage drop	<2 V closed)
Current consumption	010 mA no-load
Maximum delay first up	5 ms
Maximum delay response	0.2 ms
Maximum delay recovery	0.2 ms
Marking	CE
Threaded length	1.02 in (26 mm)
Maximum Height	0.31 in (8 mm)
Length	1.65 in (42 mm)
Net Weight	0.03 lb(US) (0.015 kg)

#### Environment

Product certifications	UL CSA
Ambient air temperature for operation	-13122 °F (-2550 °C)
Ambient air temperature for storage	-40185 °F (-4085 °C)
Vibration resistance	25 gn +/- 2 mm 1055 Hz)IEC 60068-2-6
Shock resistance	50 gn 11 ms IEC 60068-2-27

### Ordering and shipping details

Category	22486 - SENSORS, PROXIMITY
Discount Schedule	DS2
GTIN	00785901911159
Nbr. of units in pkg.	1
Package weight(Lbs)	0.09 lb(US) (0.04 kg)
Returnability	No
Country of origin	FR

### Packing Units

racking office	
Unit Type of Package 1	PCE
Package 1 Height	1.61 in (4.1 cm)
Package 1 width	2.56 in (6.5 cm)
Package 1 Length	3.74 in (9.5 cm)
Unit Type of Package 2	BAG
Number of Units in Package 2	1
Package 2 Weight	1.02 oz (29 g)
Package 2 Height	0.31 in (0.8 cm)
Package 2 width	7.87 in (20 cm)
Package 2 Length	5.91 in (15 cm)
Unit Type of Package 3	S01
Number of Units in Package 3	9
Package 3 Weight	12.20 oz (346 g)
Package 3 Height	5.91 in (15 cm)
Package 3 width	5.91 in (15 cm)
Package 3 Length	15.75 in (40 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

### Contractual warranty

14.	10 11
Warranty	18 months
	10 111011110