

## Product data sheet

### Characteristics

# 8538SCG33S8V03

NEMA Combination Starter, Type S, 60A  
fusible disconnect, Size 1, 27A, 7.5 HP at 240  
VAC polyphase, 240 VAC coil, NEMA 1

### Main

Contactors application	Non-reversing
Device short name	S

### Complementary

Maximum Depth	8.34 in (211.84 mm)
Device mounting	Surface
Fuse type	R
Maximum Height	22.5 in (571.50 mm)
NEMA size	1
Number of poles	3
Number of thermal units required	3
Net Weight	38 lb(US) (17.24 kg)
Maximum Width	9.5 in (241.30 mm)

### Environment

NEMA degree of protection	NEMA 1
Product certifications	CSA LR584 class 3211 04 UL listed file E152395 CCN NKJH7

### Ordering and shipping details

Category	21213 - 8538,39 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
Nbr. of units in pkg.	1
Package weight(Lbs)	45 lb(US) (20.41 kg)
Returnability	No
Country of origin	MX

### Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

### Contractual warranty

Warranty	18 months
----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the company. It is not intended to be used as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.