

SUVT SBP XFM10K30G

APC Smart-UPS VT Input Transformer MCCB

480/208 10-30kVA Floormount



Main

Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient air temperature for storage	32...113 °F (0...45 °C)
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Maximum Depth	32.95 in (83.7 cm)
Maximum Height	58.54 in (148.7 cm)
Nominal Input Voltage	3 phase
Input Frequency	60 Hz
Operating altitude	0...10000 ft
Output voltage	208 V 3 phase
Net Weight	731.94 lb(US) (332 kg)
Provided equipment	Installation guide User Manual
Relative humidity	0...95 %
Storage altitude	0...30000 ft (0.00...9144.00 m)
Maximum Width	13.82 in (35.1 cm)
Mounting mode	Not rack-mountable
Mounting preference	No preference
Mounting support	Floor
UPS size	S
Curve X-axis minimum	0 %
Maximum configurable power in VA	30000 VA
Standards	UL 1778
Rated power in VA	30000 VA

Ordering and shipping details

GTIN	00731304277217
Package weight(Lbs)	804.69 lb(US) (365 kg)

Packing Units

Package 1 Height	65.50 in (166.37 cm)
Package 1 width	28.50 in (72.39 cm)
Package 1 Length	43.50 in (110.49 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------
