

Product data sheet

Characteristics

70-124-1

Socket, Legacy general purpose relay
accessory, 3PDT, 15A, 300 V, 11 pins, solder
terminal, 788R series



Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 788XBXR/XCXR
Number of terminals	11
Switch function	3PDT
Contact composition	3 NO + 3 NC

Complementary

Line Rated Current	15 A
Rated voltage	300 V
Contact terminal arrangement	Mixed
Connections - terminals	Solder terminal
Fixing mode	By screw chassis By screw panel
Net Weight	0.43 oz (12.1 g)
Width	1.50 in (38.1 mm)
Depth	2.03 in (51.45 mm)

Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
IP degree of protection	IP20
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

Ordering and shipping details

GTIN	03606480277757
------	----------------

Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.