G55TE-BB60K30

MGE Galaxy 5500 E Backup Time Blocks & C Breaker 60kVA 30mn Off Shore & Marine





Overview

| ks, circuit breaker, isor. The cabinets are sku for marine battery xxK30 composed of |
|--|
| ted Lead Times |
| |

General

| Provided equipment | User Manual |
|--------------------|-------------|
| | |

Physical

| Maximum Depth | 31.50 in (80 cm) |
|----------------|--------------------------|
| Maximum Height | 33.46 in (85 cm) |
| Net Weight | 2685.23 lb(US) (1218 kg) |
| Maximum Width | 78.74 in (200 cm) |

Conformance

| Product certifications | CE |
|------------------------|----|
|------------------------|----|

Environmental

| Ambient air temperature for operation | 32104 °F (040 °C) |
|---------------------------------------|---------------------------|
| Operating altitude | 03333 ft |
| Relative humidity | 095 % |
| Ambient air temperature for storage | -4113 °F (-2045 °C) |
| Storage altitude | 012000 ft (0.003657.60 m) |

Batteries & Runtime

| Battery Slots Empty | 0 |
|--------------------------|------|
| Included Battery Modules | 0 |
| Battery type | VRLA |

Ordering and shipping details

| GTIN | 00731304317883 |
|---------------------|--------------------------|
| Package weight(Lbs) | 2740.35 lb(US) (1243 kg) |

Packing Units

| · doming or mo | | |
|------------------|-------------------|--|
| Package 1 Height | 39.37 in (100 cm) | |
| Package 1 width | 78.74 in (200 cm) | |
| Package 1 Length | 31.50 in (80 cm) | |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| EU RoHS Directive | Under investigation | |
|----------------------|--------------------------|--|
| | | |
| Contractual warranty | | |
| Warranty | 1 year repair or replace | |