

8903LXG60V06R6

8903LX mechanically held lighting contactor, 6 P, 6 NO, 30 A, 600 V, 440/480 V 50/60 Hz coil, NEMA 1



Main

| | |
|---------------------------|--------------------------------------|
| Product or component type | Mechanically Held Lighting Contactor |
| Range of product | 8903LX |
| Control Circuit | Separate control circuit |

Complementary

| | |
|-----------------------|--|
| Control Voltage | 440 V AC 50 Hz 480 V AC 60 Hz |
| Inrush power in VA | 180 VA 60 Hz 170 VA 50 Hz 25 VA 50/60 Hz |
| Current Rating | 20 A tungsten 30 A fluorescent |
| Number of Poles | 6P 6 NO |
| Control Unit | No control units |
| Pilot Light | No indicator |
| Other Options | 2P relay (1 NO + 1 NC) |
| Electrical connection | Screw-clamp terminals |
| Maximum Height | 12.68 in (322 mm) |
| Maximum Depth | 6.02 in (153 mm) |
| Maximum Width | 7.80 in (198 mm) |

Environment

| | |
|------------------------|------------------------------------|
| Enclosure Type | NEMA 1 painted sheet steel surface |
| Product certifications | UL Listed CSA |

Ordering and shipping details

| | |
|---------------------|-------------------------|
| Category | 21322 - 8903 LX (NOT L) |
| Discount Schedule | CP1 |
| Package weight(Lbs) | 11 lb(US) (4.99 kg) |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |
| Environmental Disclosure |  Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|