

Main

Product or component type	Starter
Type	S
Control Circuit Type	Separate control circuit

Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	18 A
Number of Poles	4P
Number of Phases	2 phases
Horsepower Rating	3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	No control units
Thermal overload type	Melting alloy 2
Electrical connection	Screw clamp terminals
NEMA size	0
Maximum Height	13.50 in (343 mm)
Maximum Depth	8.54 in (217 mm)
Maximum Width	6.38 in (162 mm)

Environment

Enclosure Type	NEMA 12 painted sheet steel
Product certifications	NEMA UL Listed CSA

Ordering and shipping details

Category	21191 - 8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
Package weight(Lbs)	12 lb(US) (5.44 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Will be compliant – Date to be confirmed
-------------------	--

Contractual warranty

Warranty	18 months
----------	-----------