



Main

Product range	Legacy
Product type	Socket
Product compatibility	Relay 750XCXR Relay 750XCXH
Number of terminals	11
Switch function	3PDT
Contact composition	3 NO + 3 NC

Complementary

Line Rated Current	5 A 15 A
Rated voltage	300 V 600 V
Contact terminal arrangement	Mixed
Connections - terminals	Output screw clamp terminalssolid Output screw clamp terminalsstranded
Tightening torque	Chassis 0.8 N.m, AWG 14...AWG 12, copper Screw < 1 N.m Screw < 0.8 N.m
Fixing mode	By screw M3.5, M3.5 panel By screws, M3 panel
Shape of screw head	Combination roundhead
Net Weight	2.01 oz (57 g)
Width	2.32 in (59 mm)
Depth	2.24 in (57 mm)

Environment

Ambient air temperature for storage	-40...221 °F (-40...105 °C)
Ambient temperature range - operational	-40...131 °F (-40...55 °C)
Flame retardance	UL94-V0
Product certifications	UL CSA CE RoHS

Ordering and shipping details

GTIN	03606480277979
------	----------------

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.