



Main

Product	Double Throw Safety Switch
Current Rating	200 A
Certifications	UL listed file E2875
Enclosure Rating	NEMA 1 steel
Factory Installed Neutral	Neutral (factory installed)
Disconnect Type	Non-fusible disconnect switch
Mounting Type	Surface
Number of Poles	2
Voltage Rating	240 V AC 250 V DC
Wire Size	AWG 6...300 kcmil aluminium/copper

Complementary

Maximum Horse Power Rating	15 hp 240 V AC 1 phase NEC 240.6
Maximum Width	23.88 in (606.55 mm)
Maximum Height	30.88 in (784.35 mm)
Maximum Depth	11.75 in (298.45 mm)
Tightening torque	340 lbf.in (38.41 N.m) AWG 6...300 kcmil

Ordering and shipping details

Category	00033 - DT SWITCH,NEMA1
Discount Schedule	DE1
GTIN	00785901310785
Nbr. of units in pkg.	1
Package weight(Lbs)	10 lb(US) (4.54 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------