

# Product data sheet

## Characteristics

# BMXXSP0800

shielding connection kit - for M340 rack - 8 slots



### Main

|                                       |                          |
|---------------------------------------|--------------------------|
| Range of product                      | Modicon X80              |
| Accessory / separate part type        | Shielding connection kit |
| Product compatibility                 | BMXXBP0800               |
| Accessory / separate part destination | Rack                     |
| Number of slots                       | 8                        |

### Complementary

|                 |                              |
|-----------------|------------------------------|
| Kit composition | Two sub-bases<br>A metal bar |
| Net Weight      | 0.75 lb(US) (0.34 kg)        |

### Ordering and shipping details

|                       |                       |
|-----------------------|-----------------------|
| Category              | 18160 - MODICON M340  |
| Discount Schedule     | PC34                  |
| GTIN                  | 00785901793014        |
| Nbr. of units in pkg. | 1                     |
| Package weight(Lbs)   | 0.82 lb(US) (0.37 kg) |
| Returnability         | Yes                   |
| Country of origin     | IT                    |

### Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Package 1 Height             | 1.81 in (4.6 cm)      |
| Package 1 width              | 3.66 in (9.3 cm)      |
| Package 1 Length             | 15.47 in (39.3 cm)    |
| Unit Type of Package 2       | S04                   |
| Number of Units in Package 2 | 24                    |
| Package 2 Weight             | 20.72 lb(US) (9.4 kg) |
| Package 2 Height             | 11.81 in (30 cm)      |
| Package 2 width              | 15.75 in (40 cm)      |
| Package 2 Length             | 23.62 in (60 cm)      |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |   |
|----------------------------|---|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|