Product data sheet Characteristics

HVLCCB20505DGL HVLCC Duplex Switch 5KV, 20IN APP B DRY XFMR LT



Main

Product	Switched fuse mechanism
Application	В
Not Included	Fuse to be ordered separately
Device application	Transformer left side

Complementary

Protection type	Fuse current limiter
Associated fuse rating	10 A E
	15 A E
	20 A E
	25 A E
	30 A E
	40 A E 50 A E
	65 A E
	80 A E
	100 A E
	125 A E
	150 A E
	175 A E
	200 A E
	250 A E 300 A E
	400 A E
	350 A E
	500 A E
Line Rated Current	600 A
Momentary Amperes Asymmetrical	40 kA
Full Load Current	300 A
Frequency	50/60 Hz
Number of Poles	3P
[Ur] highest voltage for equipment	4.76 kV
Basic Inulation Level	60 kV
Enclosure Rating	NEMA 1
Electrical connection	Lugs
Wire Gauge	AWG 2350 kcmil 2 aluminium/copper
Service Entry	UG
Enclosure Width	1016.00 mm (40 in)
Enclosure Depth	946.15 mm (37.25 in)
Enclosure Height	2286.00 mm (90 in)

Ordering and shipping details

Category	07948-DIGEST HVL/CC	
Discount Schedule	PE5A	
Package weight(Lbs)	1025.00 lb(US) (464.932 kg)	
Returnability	No	
Country of origin	US	

Contractual warranty

Marranty	40
vvairanty	18 months