# **ZBW0509**

# light block for head Ø22 for BA9s bulb 400V screw terminal for lugs





## Main

Range of product	Harmony XB4 Harmony XB5
Product or component type	Light block
Device short name	ZBW
Connections - terminals	Screw terminals for lug
Signalling type	Steady
Light source	Incandescent
Bulb base	BA 9s
Light block supply	Integrated transformer 6 V
[Us] rated supply voltage	400 V AC 50 Hz

#### Complementary

Service life	100000 h at rated voltage and 25 °C
Surge withstand	1 kV IEC 61000-4-5

#### Environment

Protective treatment	TH	
Ambient air temperature for storage	-13131 °F (-2555 °C)	
Ambient air temperature for operation	-13158 °F (-2570 °C)	
IP degree of protection	IP20 IEC 60529	
Standards	EN/IEC 60947-5-4 CSA C22.2 No 14 EN/IEC 60947-1 JIS C8201-5-1 EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-5 JIS C8201-1	
Resistance to fast transients	2 kV IEC 61000-4-4	
Resistance to electromagnetic fields	9.14 V/m (10 V/m) IEC 61000-4-3	
Resistance to electrostatic discharge	6 KV on contact (on metal parts) IEC 61000-4-2 8 kV in free air (in insulating parts) IEC 61000-4-2	
Electromagnetic emission	Class B IEC 55011	

#### Ordering and shipping details

GTIN	03389110177831	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.35 oz (10 g)	

#### **Packing Units**

Unit Type of Package 1	PCE
Package 1 Height	2.20 in (5.6 cm)
Package 1 width	1.73 in (4.4 cm)
Package 1 Length	2.13 in (5.4 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEU RoHS
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months
----------	-----------