

### Main

|                   |   |
|-------------------|---|
| Device short name | S |
|-------------------|---|

### Complementary

|                                  |                        |
|----------------------------------|------------------------|
| Rated current                    | 135 A                  |
| [Ue] rated operational voltage   | 480 V AC               |
| [Uc] control circuit voltage     | 480 V AC               |
| Maximum Depth                    | 16 in (406.40 mm)      |
| Device mounting                  | Surface                |
| Maximum Height                   | 75 in (1905.00 mm)     |
| Maximum Horse Power Rating       | 75 hp                  |
| NEMA size                        | 4                      |
| Number of poles                  | 3                      |
| Number of thermal units required | 3                      |
| Net Weight                       | 560 lb(US) (254.01 kg) |
| Maximum Width                    | 32 in (812.80 mm)      |

### Environment

|                           |                                |
|---------------------------|--------------------------------|
| NEMA degree of protection | NEMA 4                         |
| Product certifications    | UL listed file E70074 CCN NLDX |

### Ordering and shipping details

|                     |                        |
|---------------------|------------------------|
| Category            | 21231 - 8606 (NOT S*K) |
| Discount Schedule   | CP1                    |
| Package weight(Lbs) | 550 lb(US) (249.48 kg) |
| Returnability       | No                     |
| Country of origin   | MX                     |

### Offer Sustainability

|                   |               |
|-------------------|---------------|
| EU RoHS Directive | Not compliant |
|-------------------|---------------|