



### Main

Product or component type	Controllers separate parts
Accessory / separate part category	Control accessories
Product specific application	Medium hoisting applications Heavy hoisting applications
Product compatibility	XKM XKD
Accessory / separate part type	Potentiometer
Condition of use	For applications requiring an extended neutral zone
Ohmic value	4700 Ohm
Size	15 mm

### Complementary

Standards	UTE 93-265
Potentiometer characteristic	Continuous rotational operation Linear function
Operating angle	360 °
Mechanical durability	3000000 cycles
Centre tap	Wired out to terminal
Centre tap dead zone	30 °
Power dissipation in W	3 W 185 °F (85 °C)
Connections - terminals	Flying leads from soldered standard tags
Net Weight	0.12 lb(US) (0.055 kg)

### Environment

Mounting mode	By the body
---------------	-------------

### Ordering and shipping details

Category	22474 - PUSHBUTTON,CRANE JOYSTICKS
Discount Schedule	I
GTIN	03389110601336
Nbr. of units in pkg.	1
Package weight(Lbs)	0.14 lb(US) (0.06 kg)
Returnability	No
Country of origin	FR

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.36 in (6 cm)
Package 1 width	2.20 in (5.6 cm)
Package 1 Length	1.73 in (4.4 cm)
Unit Type of Package 2	S01
Number of Units in Package 2	24
Package 2 Weight	3.61 lb(US) (1.637 kg)
Package 2 Height	5.91 in (15 cm)

Package 2 width	5.91 in (15 cm)
Package 2 Length	15.75 in (40 cm)

## Offer Sustainability

EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------