



Main

Range	Spacial
Product name	Spacial SBM
Device application	Multi-purpose
Category	Industrial box
Device short name	SBMC
Enclosure type	Entry box
Enclosure nominal height	11.81 in (300 mm)
Enclosure nominal width	11.81 in (300 mm)
Enclosure nominal depth	4.72 in (120 mm)
Enclosure mounting	Wall mounted
Device composition	4 cover screw 1 cover 1 body 4 FL21 cable gland plate
Body type	Single piece body folded and welded
Type of front cover	Plain door
Cover fixing	Half turn metal screw
Lock type	Captive screw PZ2 outside sealed area
Removable parts	Cover by captive screws Cable gland plate screw

Complementary

Material	Sheet steel
Surface finish	Polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product certifications	UL BV GL LR DNV
IP degree of protection	IP55 IEC 60529
IK degree of protection	IK10 IEC 62262
Ambient air temperature for storage	-31...140 °F (-35...60 °C)
Operating temperature	-31...176 °F (-35...80 °C)
Net Weight	10.32 lb(US) (4.68 kg)

Ordering and shipping details

Category	80033 - ENCLOSURE SYSTEMS POLYESTER
Discount Schedule	ES1
GTIN	03606480520358
Nbr. of units in pkg.	1
Package weight(Lbs)	10.31 lb(US) (4.68 kg)
Returnability	No
Country of origin	IN

Packing Units

Package 1 Height	12.60 in (320.000 mm)
Package 1 width	12.60 in (320.000 mm)
Package 1 Length	5.51 in (140.000 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------