



### Main

Product or component type	Circuit breaker
Range of product	I-Line
Trip Unit Type	Thermal-magnetic
Rating Code	A

### Complementary

Line Rated Current	125 A
Number of Poles	2P
Interrupt Rating	42 KA 120 V AC 42 KA 240 V AC 30 KA 480Y/277 V AC 10 kA 250 V DC
[Ue] rated operational voltage	600 V AC 250 V DC
Mounting mode	I-Line
Electrical connection	Lugs load I-Line connection line
Wire Gauge	AWG 1...600 kcmil aluminium/copper)1 AWG 1...250 kcmil aluminium/copper)2
Terminal Type	AL400LA
Magnetic hold current	625 A
Magnetic tripping current	1250 A
Wiring configuration	4-wire
Phase connection	BC
Maximum Height	11 in (279.40 mm)
Maximum Width	6 in (152.40 mm)
Maximum Depth	5.84 in (148.34 mm)

### Environment

Product certifications	CSA UL Listed
------------------------	------------------

### Ordering and shipping details

Category	01040 - LA/LH BRKR, SW, MAG-GARD
Discount Schedule	DE2
GTIN	00785901883579
Package weight(Lbs)	16 lb(US) (7.26 kg)
Returnability	Yes
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP and DIDP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------