

Main

Product or component type	Starter
Type	S
Control Circuit Type	Common control circuit

Complementary

Control Circuit Voltage	220 V AC 50 Hz 240 V AC 60 Hz
Motor starter type	Non reversing
Current Rating	270 A
Number of Poles	3P
Number of Phases	3 phase
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC
Maximum Voltage Rating	600 V AC
Control Units	Selector switch (HAND-OFF-AUTO)
Pilot Light	Red indicator on incandescent
Thermal overload type	Melting alloy 3
Electrical connection	Screw clamp terminals
NEMA size	5
Maximum Height	47.01 in (1194 mm)
Maximum Depth	13.43 in (341 mm)
Maximum Width	17.20 in (437 mm)

Environment

Enclosure Type	NEMA 12 painted sheet steel
Product certifications	UL Listed CSA NEMA

Ordering and shipping details

Category	21194 - 8502,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
Package weight(Lbs)	177 lb(US) (80.29 kg)
Returnability	No
Country of origin	MX

Offer Sustainability

EU RoHS Directive	Not compliant
-------------------	---------------

Contractual warranty

Warranty	18 months
----------	-----------