## Product data sheet Characteristics

# 9001K12J1A

selector switch Ø 30 - 2 positions - maintained incandescent





### Main

Mani	vicin i	
Range of product	Harmony 9001K	
Product or component type	Illuminated selector switch	
Device short name	9001K	
Type of operator	maintained	
Operator profile	Amber standard knob	

### Complementary

Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Net Weight	0.54 lb(US) (0.245 kg)	
Shape of signaling unit head	Round	
Operator position information	2 positions	
Contacts type and composition	Without contact block	
Mechanical durability	500000 cycles	
Light block supply	Via integral transformer	
Light source	incandescent	
Bulb base	BA 9s	-
[Us] rated supply voltage	110120 V AC 50/60 Hz	
Device presentation	Basic element	

#### Environment

Environment	
Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Electrical shock protection class	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 6
Standards	JIS C 852 JIS C 4520 CSA C22.2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 UL 508
Product certifications	UL 508 NEMA
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27

## Ordering and shipping details

Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
Package weight(Lbs)	0.55 lb(US) (0.25 kg)
Returnability	No
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds which is known to the State of California to cause Carcinogen & Reproductive harm. For more information go to www.p65warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months	