

Main

| | |
|-----------------------|--|
| Product | General Purpose Current Transformer |
| Certifications | CSA UL Recognized |
| Ratio | 250/5 |
| Enclosure Type | NEMA 1 |
| Phase | 1 phase |
| Power Rating | 2.5 VA 60 Hz 5 VA 400 Hz 5 VA 60 Hz 10 VA 400 Hz 12.5 VA 60 Hz 25 VA 400 Hz |
| Electrical Connection | Flying leadsAWG 16 |
| Opening Size | Ø 57 mm |

Complementary

| | |
|------------|----------------------|
| Net Weight | 3.31 lb(US) (1.5 kg) |
|------------|----------------------|

Ordering and shipping details

| | |
|---------------------|---------------------------------|
| Category | 15500-CLASS 4210 CT'S (LC 5101) |
| Discount Schedule | PA1 |
| Package weight(Lbs) | 3.30 lb(US) (1.497 kg) |
| Returnability | No |
| Country of origin | MX |

Offer Sustainability

| | |
|----------------------------|---|
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.